

Better chemistry. Better business.

Hubbard-Hall Inc. • 563 South Leonard Street, Waterbury, CT 07608 • HubbardHall.com • 800-648-3412

Product Bulletin

Product Name: Metal Guard 270 Product Code: 2502070 Revision Date: June 1, 2020

Metal Guard® 270

Metal Guard 270 is an outstanding oil based, water displacing, non-staining rust preventive that will rapidly separate water displaced from metal surfaces following machining or cleaning operations. This product is designed to apply an ultra-thin highly protective film on ferrous or non-ferrous metals.

Metal Guard 270 can be applied by dipping parts while they are still wet from final rinse stage, since the displaced water rapidly settles to the bottom of the tank where it is periodically drawn off.

Metal Guard 270 films may be applied to the substrate by dipping, spraying or brushing and prevent atmospheric corrosion even under conditions of high humidity.

Features & Benefits

Rapid water	Improved corrosion protection
displacement	
High flashpoint & barium	Improved safety
free	
Low odor	Better working environment

Physical Data

Specific gravity	0.93
Vapor pressure	<0.0001
Percentage of volatility by volume	none
Vapor density (air=1)	11
Evaporation rate (ether=1)	Very low
Solubility	Not soluble
Appearance and odor	Clear oily amber liquid









Better chemistry. Better business.

Hubbard-Hall Inc. • 563 South Leonard Street, Waterbury, CT 07608 • HubbardHall.com • 800-648-3412

Product Bulletin

Product Name: Metal Guard 270 Product Code: 2502070 Revision Date: June 1, 2020

Typical Applications

- Final rust preventative after Black Magic coatings
- Final rust preventative after machining or cleaning operations
- Final rust preventative after Hubbard Hall's Mi-Phos zinc or manganese phosphate coatings

Caution

Read and understand the OSHA safety data sheet prior to handling or working with this product.

Combustible material. Keep away from open flames. Do not use cutting torch on empty containers. Harmful or fatal if swallowed. Contains petroleum distillates. Use with adequate ventilation. Avoid prolonged contact with skin. If swallowed, do not induce vomiting and call physician immediately.

People handling and using this product should be properly trained in the safe handling and use of flammable and combustible materials.

WARRANTY: THE QUALITY OF THIS PRODUCT IS GUARANTEED ON SHIPMENT FROM OUR PLANT. IF THE USE RECOMMENDATIONS ARE FOLLOWED, DESIRED RESULTS WILL BE OBTAINED. SINCE THE USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, NO GUARANTEE EXPRESSED OR IMPLIED IS MADE AS TO THE EFFECTS OF SUCH USE, OR THE RESULTS TO BE OBTAINED.

Our people. Your problem solvers.

For more information on this process please call us at 1-800-648-3412

or techservice@hubbardhall.com











